

# KM-1635/KM-2035

MONOCHROME A3 DIGITAL COPIERS WITH PRINTING OPTION

► print ► copy ► scan ► fax

## PRODUCTIVE WORKGROUP COPIERS WITH MORE INSIDE THAN MEETS THE EYE.

Where efficiency and productivity are essential to your workgroup environment, these fast multifunctional systems will take the load with ease. Numerous digital copy functions and paper handling options make them the spare hands around the office. And as an added bonus the GDI printing option turns your digital copier into an affordable printer.

- 16/20 pages per minute in A4, 8/10 pages per minute in A3
- Optional GDI printer functionality
- Time to first copy: 5.9 seconds from power on
- 32 MB RAM for full digital functionality including scan-once-print-many
- Optional duplex document processor for up to 50 sheets
- Long-life components, easy maintenance

Product depicted includes optional extras



The user-friendly display (LED + 2-line LCD) offers quick access to all digital features.



Fill trays less frequently by adding paper capacity of up to 1,250 sheets.

The GDI functionality allows printing from any Windows PC.



# KM-1635/KM-2035

MONOCHROME A3 DIGITAL COPIERS WITH PRINTING OPTION

The KM-1635 and KM-2035 incorporate extremely durable components that guarantee smooth and reliable operation. The systems are designed to last for extremely long hardware maintenance cycles. Thus, the KM-1635 and KM-2035 keep your overall operating costs low and productivity high – at the same time ensuring a minimum impact on the environment.

## GENERAL

**Technology:** Kyocera Laser, Mono component

**Engine speeds:**

KM-1635: Max. 16/8 pages per minute A4/A3

KM-2035: Max. 20/10 pages per minute A4/A3

**Resolution:** 600 x 600 dpi, 256 greyscales

**Time to first copy:** 5,9 seconds or less

**Warm-up time:** 20 seconds or less from power on

**Duty cycle:**

KM-1635: Max. 20,000 pages per month

KM-2035: Max. 30,000 pages per month

**Power source:** AC 220 ~ 240 V, 50/60 Hz

**Power consumption:** Copying: 461 W, Stand-by: 104 W,

Power-Saving (ECOpower): 43 W

**Noise (ISO 7779):** Copying: 64 dB(A), Stand-by: 40 dB(A),

Power-Saving (ECOpower): Immeasurably low

**Dimensions (W x D x H):** 574 x 552 x 502 mm

**Weight:** Main unit: Approx. 39 kg

**Certifications:** TÜV/GS, CE

This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

## PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental condition.

**Input capacity:** 300-sheet universal paper cassette, 64-105g/m<sup>2</sup>, A3, A4, A5, Ledger, Letter, Legal, Folio  
50-sheet multi-purpose tray, 45-160g/m<sup>2</sup>, A3, A4, A5, Ledger, Letter, Legal, Folio, Custom (98 x 147 mm to 297 x 432 mm)

Max. input capacity with options: 1,250 sheets

**Output capacity:** 250 sheets face-down

## COPY FUNCTIONS

**Max. original size:** A3

**Continuous copying:** 1-999

**Memory capacity:** Standard 32 MB, 18 MB of bitmapping memory and 14 MB of image storage memory, max. 160 MB (1 empty DIMM slot for 16, 32, 64, 128 MB)

**Zoom range:** 25-400% in 1% steps

**Digital features:** Scan-once-print-many, electronic sort copy, rotate sort copy<sup>\*1</sup>, automatic paper selection, duplex copying<sup>\*2</sup>, combined inch/metric copying, layout mode (2-in-1, 4-in-1), ECOcopy mode, program key mode, management mode

<sup>\*1</sup> additional paper feeder PF-410 is required

<sup>\*2</sup> additional duplex unit DU-410 is required

**Exposure mode:** Auto, manual: 5 or 9 steps

**Image adjustments:** Text + photo, text, photo

## CONTROLLER PRINT FUNCTIONS (OPTIONAL)

**Processor:** ARM 946-S 150 MHz, FlexRISC

**Memory:** Standard 32 MB, max. 32 MB

**Emulations:** Host based printing system for Windows 98, SE, ME, 2000, XP

## INTERFACE

**Standard interface:** USB 2.0 (Hi-Speed)

## OPTIONS

**Printing system (X)**

**Paper handling**

**DP-410 Duplex document processor:**

50 sheets, duplex scan, 45-160g/m<sup>2</sup>, A3-A5R, Folio, Ledger-Statement-R

**PF-410 Paper feeder:**

300 sheets, 64-105g/m<sup>2</sup>, A3-A5R, Folio, Ledger-Statement-R (max. three PF-410 can be added to the basis-system)

**DU-410 Duplex unit:**

60-80g/m<sup>2</sup>, A3-A5R, Folio, Ledger-Statement-R

**Memory**

Max. 160 MB, 1 slot (16, 32, 64, 128 MB DIMM)

**Others**

**Platen cover (D):** Platen cover

**Cabinet:**

Wooden / metal with desk storage capacity including

castors (wheels)

CB-410 (high / wooden)

CB-415 (low / wooden)

CB-411 (high / metal)

CB-416 (low / metal)

## CONSUMABLES

**TK-410 Toner-kit:**

Microfine toner for 15,000 pages with 6% A4 coverage

Capacity of starter toner for 3,000 pages with 6% A4 coverage



Select your options to suit your needs:

DP-410 Duplex document processor

DU-410 Duplex unit

PF-410 Paper feeder

PF-410 Paper feeder



Product depicted includes optional extras

Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com

Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA